Software Defined Building: Building Automation of the Next Generation

Frank Konrad (CEO)
MICROSENS GmbH & Co. KG






- - 1 What are the driving factors for digital buildings?
 - 2 The digital building Technology of today?
 - 3 Software is the new hardware
 - 4 Light out of the network
 - 5 Security due to decentral structure

MICROSENS





The Smart City as a driver for Smart Building







What are the drivers for Digital Buildings?





Energy Consumption

and the optimization opportunity

- Worldwide, buildings account for 40% of total energy consumption and contribute a corresponding % to overall carbon emissions
- In the US alone, businesses spend about US\$100 bn on energy for their offices every year
- Smarter buildings could save (in the US) US\$20-25 bn in annual energy costs.





MICROSENS


Energy Consumption

Deutsche Gesellschaft für Nachhaltiges Bauen (German Society for sustainable building)

Certificates in Platin, Gold, Silver and Bronze.

40 criteria for sustainability out of 6 fields

- Ecology
- Economy
- Social, cultural and funct. aspects
- Technology
- Processes
- Location







Assessment Criteria





ECO1.1 Building related cost over life cycle

Target is a reasonable and consciously use of the economic resources economic resources during the whole life cycle of a building.

[..]

ECO2.1 Flexibility and conversion of use

Target is to design the building as flexible as possible and to reach a maximum conversion capability.
[..]

TEC1.4 Ability to adapt of technical systems

Target is to plan the **technical systems** in a building in that way that it is possible to adapt them with minimal efforts to **changed terms of use** or respectively **technical innovations**.

[..]


SOC1.5 Influence of the user

Target is to offer the user a maximum influence for the room conditioning in terms of ventilation, sun screens, temperature and lighting



The Digital Building today

Separate systems for different applications




- Separate networks for data and building automation
- Time-consuming planning, commissioning, maintenance, adaptation
- Security not existing




The convergence of the IT and building automations systems

Traditional solution: Individual networks

MICROSENS





Future solution: Intelligent IP standard network



Smart Building Systems

Decentral architecture


- Room based control
- Central monitoring

Simple installation

• Room by room

High reliability

 Room operates partially autonomous










One network for all applications



- Secured isolated data streams
- Simple and quick provisioning of new services

BICSI MIDDLE EAST & AFRICA

MICROSENS

Flexibility

Evolution of the light switch







light switch

- system solution
- programmable comfort functions



Smart Building System

- networked and virtual
- function defined by software





Simple light switch

- only hardware
- fixed cabling





SOFTWARE

determinates function and added value

HARDWARE

is commodity

SOFTWARE is the new **HARDWARE**





Economic Efficiency

with the example Lighting

Base Innovation 1

LED technology as efficiency engine

Base Innovation 2

Power supply out of the data network




Energy consumption Offices Germany

■ Total energy consumption lighting DE: 13,3 TWh

MICROSENS


■ Lighting: **45%** of the total electric power consumption and 13% of the total energy balance





Efficiency of Light Sources

LED is unbeatable




MICROSENS euromicron group

Source: OSRAM



Smart Lighting System

Light provided by the network




MICROSENS



Smart Lighting System

Light provided by the network









Smart Lighting System


Light provided by the network















Smart Office SystemDistributed Architecture





Smart Office SystemDistributed Architecture

Simple planning and installation

- Room by room
- No master plan required

Reliability

- Local failure has only local affect
- Local function in case of central failure

Integration in central Control Systems

- On Demand
- Open interfaces















Security

The IT Security Challenge

 $\overline{\bigcirc}$

25+%

of identified attacks in enterprises will involve IoT

K Z

256 Da**ys**

average to identify while data breaches

38%

increase in the number of detected security incidents



25 Bn

IoT Devices

48%

of incidents involved a malicious or criminal attack

6,7 m

Average costs of each data breach

Source:

In year 2020 more 25%

of identified attacks

in enterprises

will involve IoT

Gartner, 2016

PwC, "Global State of Information Security Survey, 2016
Gartner – Predicts 2016: Security of Internet of Things
Cost of Data Breach Study: Global Analysis Benchmark research sponsored
by IBM Independently conducted by Ponemon Institute LLC





Security

IT Security of the Building Network

- Secured Standard Protocols (encrypted, e.g. HTTPS)
- Port based Access Control
- Tiered User Levels
- Central Security Management





Economic Efficiency

- Energy savings: Lighting, heating, air conditioning only active when work place is in use
- Energy savings through consequent integration
 - Sensors
 - Dynamic linkage with control technology
- Prevent the waste of energy:
 - Open windows disable both heating and climatization
 - Automatic deactivation of lighting in abandoned rooms
- Optimized utilization of room capacity through dynamic allocation of workplace and meeting areas
- Beyond core times, automatic change into 'sleeping-mode'



Security

- Work place is protected (data wise and physical) against abuse
- Workplace activation requires authorisation of the allocated user; automatic deactivation in case of absence
- Detection of unauthorised behaviour causes an alarm, e.g. if user enters a prohibited area
- IT security levels for Building Automation Systems as part of IP technology include
 - secured transmission protocols,
 - port based security,
 - IP Source guard,
 - secure management, etc.



Flexibility and Comfort

- Individual configuration of the work place by the user
- Dynamic creating of user groups
- Both building and room identify their user(s)
- Interaction of various systems: building access control, alarm system, HVAC control, Lighting control, building operating system etc.
- Automation of processes:
 IF user passes slip road THEN automatic parking lot assignment,
 elevator request, dynamic allocation of working place, activation
 and configuration of both workplace and indoor climate




Reduced maintenance efforts

- Automated Fault Detection help reduce the downtime and O&M costs
- Alarm management timely and targeted interventions in case of faulty or underperforming building equipment
- Automated Diagnostics easy detection of erratic situations, fast resolution or workarounds in case of known problems



Smart Office System System Overview Smart microRTS **Director** (Soft PLC) App **LED Panel** IEC 61131-3 Twisted Pair **Smart Lighting** PoE+ Controller Blinds Control Climate Unit Light Switch EnOcean/IP500 microSys **Program Ethernet** Switch / **Enginnering** Code **Platform Smart** Twisted Pair PoE+ **Engine** DI Smart I/O Controller

MICROSENS




MICROSENS

Smart Building Solution



Smart Office System



- Work place is assigned to the user dynamically
- Network access and user specific functions are activated

Economic Efficiency

 Energy savings: Lighting, Heating, Air Conditioning only active when work place is in use

Security

■ IT security levels for Building Automation Systems as part of IP technology include secured transmission protocols & port based security

Flexibility and Comfort

- Individual configuration of the work place by the user
- Dynamic creating of user groups



